



**Properties and applications**

The 220mm duct lid (Part No: TC1279-22SN) is a snap fit onto 220mm straight duct (Part No: TC1279-21). The lid is quickly and easily fitted and removed from 220mm straight duct, when required. Both the lid and duct are made of tough Noryl plastic with a non-halogen fire retardant. The duct connects to other duct sections and various bends, adapters, etc, using either: a standard joiner (Part No: TC1279-25; Telstra S 353/00515) or a slotless joiner (Part No: TC1279-250A); which are available separately. A 220mm duct carries up to 800 x Ø3mm optical fibre cords to a depth of 50mm, without causing excessive crushing or stress on them. This is the maximum recommended number of optical fibre cords for 220mm duct.

**Benefits & features**

- Cover (Part No: TC1279-22SN), snaps onto 220mm duct (Part No: TC 1279-21); included
- Clips straight into joiner
- Tough, fire retardant material
- Joiners (Part No: TC1279-25; Telstra: S 353/00515 or Part No: TC1279-250A); available separately
- Purchase by the unit

**Material**

Fire retardant plastic, Halogen free, UL94-V0 rated

**Dimensions & weights:**

**Weight:**

Lid: 1.99 kg; Duct: 2.90 kg; Duct & Lid: 4.89 kg

**Dimensions:**

Lid: 235mm (W) x 15mm (H) x 2000mm (D)  
 Duct: 235mm (W) x 115mm (H) x 2000mm (D)

Yellowduct® is a registered Warren & Brown Technologies

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
		L. Brücher		001			

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger OSI GmbH & Co. OHG