



Properties and applications

The slotless joiner is used to link standard 220mm straight ducting with itself or any of the other 220mm components; with which it provides a smooth & strong joint. Typical other fittings are: horizontal or vertical elbows, cross connectors, tees, etc.; which require a joiner at each interface. The slotless joiner incorporates three metal spring brackets, which securely grip with the flat face of the mating 220mm duct components. This ensures that a positive, permanent connection is achieved. The slotless joiner is easily and simply locked or released by turning the locking slot through 90°; using either a coin or wide bladed screwdriver.

Benefits & features

- Quickly installed on 220mm duct components, to achieve a positive connection
- Quickly released, using either a coin or wide bladed screwdriver
- Incorporates 4 spring brackets, that make a permanent connection between 220mm duct components
- Tough, fire retardant material
- Purchase by the unit

Material

Fire retardant plastic, Halogen free, UL94-V0 rated

Dimensions & weights

Weight:
116g

Dimensions:
50mm (W) x 100mm (H) x 246mm (D)

Yellowduct® is a registered trademark of Warren & Brown Technologies

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
		L. Brücher		001			